

CAM-6510



- 1/4" EXviewHAD
- Day and night function with Mechanical IR Cut Filter
- Optical Zoom Ratio 18X
- 0.005 Lux at F1.4
- Backlight Compensation, Auto Iris Control, Auto White Balance supported
- MPEG-4 ASP compression
- CIF up to Full D1 resolution at 30/25 FPS
- Multi-stream with variable frame rate in the same compression
- Hardware motion detection, Digital Input / Output
- Fail-over network protection and QoS enabled (L3) video streaming
- Surface, flush and wall mount supported

Indoor wall mount



► Appearance



Indoor pole mount



► Appearance



Indoor corner mount



► Appearance



Indoor flush mount




► Appearance



Indoor surface mount



* For more information, please refer to Technical FAQ, TS-00004 on ACTi Website.

**PRODUCT SPECIFICATION**

CAM-6510		
Image	Device	EXviewHAD CCD
	Size	1/4 inch
	Effective Pixels (HxV)	768x494(NTSC); 752x582(PAL)
	Horizontal Resolution	480 TVL
Min. scene Illumination	Color	0.1 Lux (F1.4, 1/4s(NTSC) or 1/3s (PAL))
	B/W	0.005 Lux (F1.4, 1/4s (NTSC) or 1/3s (PAL), IR ON)
Lens	Focal Length	4.1 ~ 73.8 mm
	Zoom Ratio	18x
	Aperture Ratio	F1.4(Wide), F3.0(Tele)
	Diagonal angle	48°(W)~2.8°(T)
	Zoom Speed	2.1sec(1x to 18x)
	Digital Zoom	X1 ~ X12 variable
Synchronization	Sync. System	Internal / line lock
Day/Night Functions	Mechanical IR Cut Filter	Yes
Functions	Motion Detection	Yes (3 windows)
	Electronic Shutter	1/1 ~ 1/10,000 sec. (NTSC) 1/1 ~ 1/10,000 sec. (PAL)
	Fixed Shutter	Yes
	Auto Slow Shutter	Yes
	BLC	On / Off
	AGC	Auto / Manual
	Auto Exposure Control	Auto/manual/exposure compensation
	Exposure Compensation	-10.5~+10.5dB (15steps)
	White Balance	Auto / Manual
	Camera ID	Max. 20 characters
	Number of Preset	256 points
	Auto Iris Control	Auto / manual
	Sequence Group	8
	Auto Pan (patrol)	4
	Schedule	Yes
	Privacy Mask	24
	WDR	N/A
	Absolute Position	Yes
S/N Ratio	Cruise	1
	S/N Ratio	Better than 50 dB (AGC off)
PAN/TILT	Manual Speed	Pan Tilt 1° ~ 90° / sec.
	Preset Speed	Pan Tilt 5° ~ 400° / sec
	Preset Accuracy	Pan 0.225°
		Tilt 0.45°
	Travel Range	Pan 360° endless
		Tilt -10° ~ 100° (190° in Image Flip mode)
Video (Compression)	Compression	MPEG-4 ASP compliant
	Picture Resolution	Full D1 (720 x 480 in NTSC, 720 x 576 in PAL); CIF (352 x 240 in NTSC, 352 x 288 in PAL); QCIF (160 x 112 in NTSC, 176 x 144 in PAL)
	Bit Rate	28 K ~ 3 M bps
	Multi-stream	Up to 4 configurable frame rate/bit rate streams for preview and recording
Video Output	Composite Output	CVBS, 1.0Vp-p with 75 Ω loading, BNC connector
Alarm	Input	8, TTL, terminal block (optional)
	Output	1, TTL, terminal block (optional)
Casing	Vandal Proof	Yes (cover with vandal proof option)
Network	LAN Port	Ethernet (10 / 100Base-T), RJ-45 connector
	WAN Port	Ethernet (10 / 100Base-T), RJ-45 connector
	Protocol	TCP, UDP, IP, HTTP, DHCP, PPPoE, RTP, RTSP, FTP, SMTP, DNS, DDNS, NTP, ICMP, IGMP, ARP
Software	Web Browser	Microsoft Internet Explorer 6.0 or above
	SDK	ACTi SDK-10000
	Security	Password protection: configured by the administrator
Operating	Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
Power	Power Requirement	AC 24 V ±20%
	Power Consumption	20 W
Physical	Dimensions (ØxH)	131 mm x 226 mm (5.2" x 8.9")
	Weight	1,600 g (3.5 lb)

* Only Pan/Tilt absolute position is supported.